



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQE 225M PG6 - 30 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 225M PG
Poles	6
kW	30
HP	40
rpm	990
Mn Nm	289.4
η 50%	92.3
η 75%	94.2
η 100%	94.
cos Phi	0.83
I _N 400V	55.4
I _N 460V	-
I _N 575V	-
I _A /I _N	6.9

M_A/M_N	2.0
M_S/M_N	2.0
M_K/M_N	2.1
$J \cdot 10^{-3} \text{ kgm}^2$	547
kg	335

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6313 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	6.300 hours
Regreasing device vertical	6.300 hours
Grease Quantity	25 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	68

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.