



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQH 80Z BA2 - 1.1 kW - 2 poles - 460V - 60Hz / 575V - 60Hz

PERFORMANCE DATA

Type	AMQH 80Z BA
Poles	2
kW	1.1
HP	1.5
rpm	3490
Mn Nm	3.0
η 50%	82.3
η 75%	85.2
η 100%	85.5
cos Phi	0.72
I_N 400V	-
I_N 460V	2.2
I_N 575V	1.8

I_A/I_N	10.3
M_A/M_N	5.5
M_S/M_N	5.3
M_K/M_N	5.8
$J \cdot 10^{-3} \text{ kgm}^2$	0.9
kg	11.1

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	60

Electrical Data

Voltage	460V - 60Hz / 575V - 60Hz
Connection	
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.