



## Motori Asincroni Trifase - IE4/IE3/IE2/IE1

### MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



## TECHNICAL DATA

Motor Type

AMPE 56Z CA2 - 0.18 kW - 2 poles - 400V - 50Hz

## PERFORMANCE DATA

| Type        | AMPE 56Z CA |
|-------------|-------------|
| Poles       | 2           |
| kW          | 0.18        |
| HP          | 0.24        |
| rpm         | 2650        |
| Mn Nm       | 0.6         |
| $\eta$ 50%  | 57.0        |
| $\eta$ 75%  | 61.8        |
| $\eta$ 100% | 65.9        |
| cos Phi     | 0.73        |
| $I_N$       | 0.60        |
| $I_A/I_N$   | 3.9         |
| $M_A/M_N$   | 3.8         |
| $M_S/M_N$   | 3.8         |

|                                          |      |
|------------------------------------------|------|
| <b>M<sub>K</sub>/M<sub>N</sub></b>       | 3.9  |
| <b>J 10<sup>-3</sup> kgm<sup>2</sup></b> | 0.09 |
| <b>kg</b>                                | 3.4  |

## Mechanical Data

|                                     |                               |
|-------------------------------------|-------------------------------|
| <b>Design</b>                       | Aluminium                     |
| <b>Degree of protection</b>         | IP 55                         |
| <b>Bearings DE/NDE</b>              | 6201/2Z                       |
| <b>Lubrication grease</b>           | low & high temperature grease |
| <b>Regreasing device horizontal</b> | permanent lubrication         |
| <b>Regreasing device vertical</b>   | permanent lubrication         |
| <b>Grease Quantity</b>              | -                             |
| <b>Cooling</b>                      | IC 411                        |
| <b>Vibration Level</b>              | A (normal)                    |
| <b>Noise Lpa db(A)</b>              | 48                            |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Voltage</b>               | 400V - 50Hz    |
| <b>Connection</b>            | ?/Y 230/400V   |
| <b>Duty type</b>             | S1             |
| <b>Thermal protection</b>    | na             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -20°C / +40 °C |
| <b>Altitude</b>              | 1000 m.a.s.l.  |