



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMPE 63Z BA4 - 0.18 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

| | |
|------------------------------------|-------------|
| Type | AMPE 63Z BA |
| Poles | 4 |
| kW | 0.18 |
| HP | 0.25 |
| rpm | 1360 |
| Mn Nm | 1.3 |
| η 50% | 61.8 |
| η 75% | 67.0 |
| η 100% | 69.9 |
| cos Phi | 0.66 |
| I_N | 0.6 |
| I_A/I_N | 2.3 |
| M_A/M_N | 1.9 |
| M_S/M_N | 1.8 |

| | |
|--|-----|
| M_K/M_N | 1.9 |
| J 10⁻³ kgm² | 0.3 |
| kg | 4.1 |

Mechanical Data

| | |
|-------------------------------------|-------------------------------|
| Design | Aluminium |
| Degree of protection | IP 55 |
| Bearings DE/NDE | 6202/2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device horizontal | permanent lubrication |
| Regreasing device vertical | permanent lubrication |
| Grease Quantity | - |
| Cooling | IC 411 |
| Vibration Level | A (normal) |
| Noise Lpa db(A) | 38 |

Electrical Data

| | |
|------------------------------|----------------|
| Voltage | 400V - 50Hz |
| Connection | ?/Y 230/400V |
| Duty type | S1 |
| Thermal protection | na |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -20°C / +40 °C |
| Altitude | 1000 m.a.s.l. |