



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type AMPE 100L AA4 - 2.2 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 100L AA
Poles	4
kW	2.2
HP	3
rpm	1455
Mn Nm	14.4
η 50%	83.2
η 75%	86.2
η 100%	86.7
cos Phi	0.63
I_N	5.9
I_A/I_N	7.2
M_A/M_N	3.7
M_S/M_N	3.0

M_K/M_N	3.9
J 10⁻³ kgm²	5.9
kg	22.8

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	50

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.