



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMPE 132M YA6 - 4 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 132M YA
Poles	6
kW	4
HP	5.5
rpm	975
Mn Nm	39.2
η 50%	85.2
η 75%	87.1
η 100%	86.8
cos Phi	0.70
I_N	9.6
I_A/I_N	5.4
M_A/M_N	2.2
M_S/M_N	1.7

M_K/M_N	3.2
J 10⁻³ kgm²	44.4
kg	46

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	57

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V - ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.