



**Motori Asincroni Trifase - IE4/IE3/IE2/IE1**

**MOTORI PREMIUM EFFICIENCY - IE3/CURUS**

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



**TECHNICAL DATA**

**Motor Type**

AMPE 160L TA6 - 11 kW - 6 poles - 400V - 50Hz

**PERFORMANCE DATA**

|                                    |              |
|------------------------------------|--------------|
| <b>Type</b>                        | AMPE 160L TA |
| <b>Poles</b>                       | 6            |
| <b>kW</b>                          | 11           |
| <b>HP</b>                          | 15           |
| <b>rpm</b>                         | 970          |
| <b>Mn Nm</b>                       | 108.3        |
| $\eta$ 50%                         | 89.1         |
| $\eta$ 75%                         | 90.4         |
| $\eta$ 100%                        | 90.3         |
| <b>cos Phi</b>                     | 0.78         |
| <b>I<sub>N</sub></b>               | 22.9         |
| <b>I<sub>A</sub>/I<sub>N</sub></b> | 8.0          |
| <b>M<sub>A</sub>/M<sub>N</sub></b> | 2.7          |
| <b>M<sub>S</sub>/M<sub>N</sub></b> | 2.4          |

|  |       |
|--|-------|
| <b><math>M_K/M_N</math></b>              | 3.2   |
| <b>J 10<sup>-3</sup> kgm<sup>2</sup></b> | 136.0 |
| <b>kg</b>                                | 105   |

## Mechanical Data

|                                     |                               |
|-------------------------------------|-------------------------------|
| <b>Design</b>                       | Aluminium                     |
| <b>Degree of protection</b>         | IP 55                         |
| <b>Bearings DE/NDE</b>              | 6309/2Z                       |
| <b>Lubrication grease</b>           | low & high temperature grease |
| <b>Regreasing device horizontal</b> | permanent lubrication         |
| <b>Regreasing device vertical</b>   | permanent lubrication         |
| <b>Grease Quantity</b>              | -                             |
| <b>Cooling</b>                      | IC 411                        |
| <b>Vibration Level</b>              | A (normal)                    |
| <b>Noise Lpa db(A)</b>              | 58                            |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Voltage</b>               | 400V - 50Hz    |
| <b>Connection</b>            | ?/Y 400/690V   |
| <b>Duty type</b>             | S1             |
| <b>Thermal protection</b>    | na             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -20°C / +40 °C |
| <b>Altitude</b>              | 1000 m.a.s.l.  |