



### Motori Asincroni Trifase - IE4/IE3/IE2/IE1

### MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



## TECHNICAL DATA

Motor Type

AMPH 132M TA2 - 9.2 kW - 2 poles - 460V - 60Hz

## PERFORMANCE DATA

Type	AMPH 132M TA
Poles	2
kW	9.2
HP	12.4
rpm	3545
Mn Nm	24.8
$\eta$ 50%	87.7
$\eta$ 75%	90.1
$\eta$ 100%	90.2
cos Phi	0.88
$I_N$	14.5
$I_A/I_N$	10.0
$M_A/M_N$	4.0
$M_S/M_N$	3.5

<b>M<sub>K</sub>/M<sub>N</sub></b>	4.7
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	25.0
<b>kg</b>	50

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6208/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Grease Quantity</b>	-
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	72

## Electrical Data

<b>Voltage</b>	460V - 60Hz
<b>Connection</b>	YY/Y 230/460V - ? 460V
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.