



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2/CURUS

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMHE 132M ZA2 - 9.2 kW - 2 poles - 400V - 50Hz / 460V - 60Hz

PERFORMANCE DATA

Type	AMHE 132M ZA
Poles	2
kW	9.2
HP	12.5
rpm	2920
Mn Nm	30.1
η 50%	88.4
η 75%	89.9
η 100%	90.0
cos Phi	0.87
I_N	16.9
I_A/I_N	9.4
M_A/M_N	3.2

M_S/M_N	3.0
M_K/M_N	3.8
J 10⁻³ kgm²	17.5
kg	58.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	72

Electrical Data

Voltage	400V - 50Hz / 460V - 60Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.