



Motori Autofrenanti - IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMHEBY 90L CA2 - 2.2 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

| | |
|------------------------------------|---------------|
| Type | AMHEBY 90L CA |
| Poles | 2 |
| kW | 2.2 |
| HP | 3 |
| rpm | 2860 |
| Mn Nm | 7.3 |
| η 50% | 82.5 |
| η 75% | 84 |
| η 100% | 84 |
| cos Phi | 0.85 |
| I_N | 4.4 |
| I_A/I_N | 8.5 |
| M_A/M_N | 3.5 |
| M_K/M_N | 3.7 |

| | |
|--|---------------------|
| J 10⁻³ kgm² | 2.13 |
| Mb max Nm | 15(40) ² |
| zL 1) c/h | 2700 |
| kg | 26.1 |

Mechanical Data

| | |
|-------------------------------------|-------------------------------|
| Design | Aluminium |
| Degree of protection | IP 55 |
| Bearings DE/NDE | 6205/2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device horizontal | permanent lubrication |
| Regreasing device vertical | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |
| Noise Lpa db(A) | 62 |

Electrical Data

| | |
|------------------------------|----------------|
| Voltage | 400V - 50Hz |
| Connection | ?/Y 230/400V |
| Duty type | S1 |
| Thermal protection | na |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -20°C / +40 °C |
| Altitude | 1000 m.a.s.l. |