



**Motori Autofrenanti - IE3/IE2/IE1**

**MOTORI HIGH EFFICIENCY - IE2**

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



**TECHNICAL DATA**

**Motor Type** AMHEBZ 63Z AA2 - 0.18 kW - 2 poles - 400V - 50Hz

**PERFORMANCE DATA**

|                                    |               |
|------------------------------------|---------------|
| <b>Type</b>                        | AMHEBZ 63Z AA |
| <b>Poles</b>                       | 2             |
| <b>kW</b>                          | 0.18          |
| <b>HP</b>                          | 0.25          |
| <b>rpm</b>                         | 2720          |
| <b>Mn Nm</b>                       | 0.6           |
| $\eta$ 50%                         | 53.8          |
| $\eta$ 75%                         | 59.7          |
| $\eta$ 100%                        | 60.4          |
| <b>cos Phi</b>                     | 0.76          |
| <b>I<sub>N</sub></b>               | 0.6           |
| <b>I<sub>A</sub>/I<sub>N</sub></b> | 3.7           |
| <b>M<sub>A</sub>/M<sub>N</sub></b> | 3.0           |
| <b>M<sub>K</sub>/M<sub>N</sub></b> | 3.1           |

|  |      |
|--|------|
| <b>J 10<sup>-3</sup> kgm<sup>2</sup></b> | 0.19 |
| <b>Mb max Nm</b>                         | 3.5  |
| <b>zL 1) c/h</b>                         | 7100 |
| <b>kg</b>                                | 5.5  |

## Mechanical Data

|                                     |                               |
|-------------------------------------|-------------------------------|
| <b>Design</b>                       | Aluminium                     |
| <b>Degree of protection</b>         | IP 55                         |
| <b>Bearings DE/NDE</b>              | 6202/2Z                       |
| <b>Lubrication grease</b>           | low & high temperature grease |
| <b>Regreasing device horizontal</b> | permanent lubrication         |
| <b>Regreasing device vertical</b>   | permanent lubrication         |
| <b>Cooling</b>                      | IC 411                        |
| <b>Vibration Level</b>              | A (normal)                    |
| <b>Noise Lpa db(A)</b>              | 49                            |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Voltage</b>               | 400V - 50Hz    |
| <b>Connection</b>            | ?/Y 230/400V   |
| <b>Duty type</b>             | S1             |
| <b>Thermal protection</b>    | na             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -20°C / +40 °C |
| <b>Altitude</b>              | 1000 m.a.s.l.  |