



Motori Autofrenanti - IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMHEBZ 112M AA2 - 4 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBZ 112M AA
Poles	2
kW	4
HP	5.5
rpm	2940
Mn Nm	13
η 50%	85.5
η 75%	87
η 100%	86.8
cos Phi	0.88
I_N	7.6
I_A/I_N	8
M_A/M_N	2.9
M_K/M_N	3.3

J 10⁻³ kgm²	7.2
Mb max Nm	40(75) ²
zL 1) c/h	950
kg	42.9

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6306/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	68

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.