



Motori Autofrenanti - IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMHES 80Z XA4 - 0.55 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

| | |
|------------------------------------|--------------|
| Type | AMHES 80Z XA |
| Poles | 4 |
| kW | 0.55 |
| HP | 0.75 |
| rpm | 1422 |
| Mn Nm | 3.8 |
| η 50% | 75.1 |
| η 75% | 77.8 |
| η 100% | 77.1 |
| cos Phi | 0.72 |
| I_N | 1.5 |
| I_A/I_N | 3.6 |
| M_A/M_N | 2.6 |
| M_K/M_N | 2.6 |

| | |
|--|------|
| J 10⁻³ kgm² | 2.37 |
| Mb max Nm | 7 |
| zL 1) c/h | 4250 |
| kg | 11 |

Mechanical Data

| | |
|-------------------------------------|-------------------------------|
| Design | Aluminium |
| Degree of protection | IP 55 |
| Bearings DE/NDE | 6204/2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device horizontal | permanent lubrication |
| Regreasing device vertical | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |
| Noise Lpa db(A) | 48 |

Electrical Data

| | |
|------------------------------|----------------|
| Voltage | 400V - 50Hz |
| Connection | ?/Y 230/400V |
| Duty type | S1 |
| Thermal protection | na |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -20°C / +40 °C |
| Altitude | 1000 m.a.s.l. |