



Motori Autofrenanti - IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type AMPEBZ 100L AA4 - 2.2 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBZ 100L AA
Poles	4
kW	2.2
HP	3
rpm	1455
Mn Nm	14.5
η 50%	86.0
η 75%	87.0
η 100%	86.7
cos Phi	0.78
I_N	4.8
I_A/I_N	9.0
M_A/M_N	3.1
M_K/M_N	3.5

J 10⁻³ kgm²	6.08
Mb max Nm	40(75) ²
zL 1) c/h	4250
kg	31.1

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	50

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.