



Motori Autofrenanti - IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMPEBY 100L AA2 - 3 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBY 100L AA
Poles	2
kW	3
HP	4
rpm	2900
Mn Nm	9.9
η 50%	82.3
η 75%	85.8
η 100%	87.1
cos Phi	0.89
I_N	5.6
I_A/I_N	8.8
M_A/M_N	5.5
M_K/M_N	4.5

J 10⁻³ kgm²	6.5
Mb max Nm	13
zL 1) c/h	950
kg	27.9

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	66

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.