

Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMBZ 90L DA2 - 3 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBZ 90L DA
Poles	2
kW	3
HP	4
rpm	2860
Mn Nm	10.02
η 50%	78.7
η 75%	81.8
η 100%	82.2
cos Phi	0.80
I_N 400 V	6.6
I_N 380-400 V	6.8
I_A/I_N	7.2
M_A/M_N	3.9

M_K/M_N	3.8
J 10 ⁻³ kgm ²	2.32
Mb max Nm	40
zL ¹⁾ c/h	2650
kg	27.2

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.