



Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type AMS 90L CA2 - 2.2 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMS 90L CA
Poles	2
kW	2.2
HP	3
rpm	2860
Mn Nm	7.35
η 50%	81.5
η 75%	82.8
η 100%	81.8
cos Phi	0.81
I_N 400 V	4.9
I_N 380-400 V	4.9
I_A/I_N	7.1
M_A/M_N	4.1

M_K/M_N	4
J 10⁻³ kgm²	2.76
Mb max Nm	7
zL 1) c/h	1200
kg	19

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.