



Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type AMS 160M VA2 - 11 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

| | |
|------------------------------------|-------------|
| Type | AMS 160M VA |
| Poles | 2 |
| kW | 11 |
| HP | 15 |
| rpm | 2940 |
| Mn Nm | 35.73 |
| η 50% | 83.4 |
| η 75% | 86.4 |
| η 100% | 87.7 |
| cos Phi | 0.83 |
| I_N 400 V | 21.9 |
| I_N 380-400 V | 22.7 |
| I_A/I_N | 7.4 |
| M_A/M_N | 2.5 |

| | |
|--|------|
| M_K/M_N | 3.1 |
| J 10⁻³ kgm² | 37.2 |
| Mb max Nm | 30 |
| zL 1) c/h | 315 |
| kg | 87 |

Mechanical Data

| | |
|-------------------------------------|-------------------------------|
| Design | ALUMINIUM |
| Degree of protection | IP 55 |
| Bearings DE/NDE | 6309/2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device horizontal | permanent lubrication |
| Regreasing device vertical | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |
| Noise Lpa db(A) | 74 |

Electrical Data

| | |
|------------------------------|----------------|
| Voltage | 400V - 50Hz |
| Connection | ?/Y 400/690V |
| Duty type | S1 |
| Thermal protection | na |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -20°C / +40 °C |
| Altitude | 1000 m.a.s.l. |