

Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMS 100L BA4 - 3 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMS 100L BA
Poles	4
kW	3
HP	4
rpm	1425
Mn Nm	20.1
η 50%	82
η 75%	83.0
η 100%	81.6
cos Phi	0.78
I_N 400 V	6.8
I_N 380-400 V	6.9
I_A/I_N	4.6
M_A/M_N	2.4

M_K/M_N	2.5
J 10 ⁻³ kgm ²	8.7
Mb max Nm	13
zL ¹⁾ c/h	2350
kg	26.8

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	50

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.