



**Motori Monofase - IE2**

**MOTORI HIGH EFFICIENCY - IE2**

- Personalizzazione a tutti i livelli



## TECHNICAL DATA

**Motor Type**

AMMEHE 100L XA2 - 1.8 kW - 2 poles - 230V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMMEHE 100L XA
<b>Poles</b>	2
<b>kW</b>	1.8
<b>HP</b>	2.5
<b>rpm</b>	2900
<b>Mn Nm</b>	5.9
$\eta$ 100%	82.2
<b>cos Phi</b>	0.98
<b>I<sub>N</sub> 230V</b>	9.5
<b>I<sub>A</sub>/I<sub>N</sub></b>	6.9
<b>M<sub>A</sub>/M<sub>N</sub></b>	2.1
<b>M<sub>K</sub>/M<sub>N</sub></b>	2.8
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	7.30
<b>kg</b>	26.5

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6206/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	66

## Electrical Data

<b>Voltage</b>	230V - 50Hz
<b>Connection</b>	230V
<b>Running Capacitor Microf</b>	40
<b>Starting Capacitor Microf</b>	124 - 149
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.