



Motori Monofase - IE2

MOTORI STANDARD

- Personalizzazione a tutti i livelli



TECHNICAL DATA

Motor Type

AMM 71Z BA2 - 0.55 kW - 2 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMM 71Z BA
Poles	2
kW	0.55
HP	0.75
rpm	2740
η 100%	69
cos Phi	0.89
I_N 230V	3.9
I_N 220-240V	4.1
I_A/I_N	3.5
M_A/M_N	0.7
M_K/M_N	1.7
$J \cdot 10^{-3} \text{ kgm}^2$	0.55
kg	8.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	16
Starting Capacitor Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.