



**Motori Monofase - IE2**

**MOTORI STANDARD**

- Personalizzazione a tutti i livelli



**TECHNICAL DATA**

**Motor Type**

AMME 71Z CA4 - 0.37 kW - 4 poles - 230V - 50Hz

**PERFORMANCE DATA**

Type	AMME 71Z CA
Poles	4
kW	0.37
HP	0.5
rpm	1370
$\eta$ 100%	62
cos Phi	0.88
$I_N$ 230V	2.8
$I_N$ 220-240V	3.1
$I_A/I_N$	2.9
$M_A/M_N$	2.5
$M_K/M_N$	1.2
$J \cdot 10^{-3} \text{ kgm}^2$	1.08
kg	8.5

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6203/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	42

## Electrical Data

<b>Voltage</b>	230V - 50Hz
<b>Connection</b>	230V
<b>Running Capacitor Microf</b>	16
<b>Starting Capacitor Microf</b>	53 - 64
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.