



Motori Monofase - IE2

MOTORI STANDARD

- Personalizzazione a tutti i livelli



TECHNICAL DATA

Motor Type

AMME 71Z AA6 - 0.15 kW - 6 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMME 71Z AA
Poles	6
kW	0.15
HP	0.2
rpm	865
η 100%	43
cos Phi	0.83
I_N 230V	1.8
I_N 220-240V	1.9
I_A/I_N	1.8
M_A/M_N	1.9
M_K/M_N	1.2
J 10^{-3} kgm ²	1.24
kg	8.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	40

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	6.3
Starting Capacitor Microf	16
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.