



**Motori Monofase - IE2**

**MOTORI STANDARD**

- Personalizzazione a tutti i livelli



**TECHNICAL DATA**

**Motor Type**

AMME 100L AA6 - 1.1 kW - 6 poles - 230V - 50Hz

**PERFORMANCE DATA**

Type	AMME 100L AA
Poles	6
kW	1.1
HP	1.5
rpm	950
$\eta$ 100%	69
cos Phi	0.96
$I_N$ 230V	7.1
$I_N$ 220-240V	7.7
$I_A/I_N$	2.4
$M_A/M_N$	1.4
$M_K/M_N$	1.3
$J \cdot 10^{-3} \text{ kgm}^2$	6.73
kg	19.0

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6206/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	51

## Electrical Data

<b>Voltage</b>	230V - 50Hz
<b>Connection</b>	230V
<b>Running Capacitor Microf</b>	40
<b>Starting Capacitor Microf</b>	161 - 193
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.