



**Motori Monofase - IE2**

**MOTORI STANDARD**

- Personalizzazione a tutti i livelli



**TECHNICAL DATA**

**Motor Type**

AMME 100L BA6 - 1.5 kW - 6 poles - 230V - 50Hz

**PERFORMANCE DATA**

<b>Type</b>	AMME 100L BA
<b>Poles</b>	6
<b>kW</b>	1.5
<b>HP</b>	2
<b>rpm</b>	870
<b><math>\eta</math> 100%</b>	66
<b>cos Phi</b>	0.98
<b>I<sub>N</sub> 230V</b>	10
<b>I<sub>N</sub> 220-240V</b>	10.2
<b>I<sub>A</sub>/I<sub>N</sub></b>	2.5
<b>M<sub>A</sub>/M<sub>N</sub></b>	2.0
<b>M<sub>K</sub>/M<sub>N</sub></b>	1.4
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	9.43
<b>kg</b>	22.5

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6206/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	51

## Electrical Data

<b>Voltage</b>	230V - 50Hz
<b>Connection</b>	230V
<b>Running Capacitor Microf</b>	50
<b>Starting Capacitor Microf</b>	161 - 193
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.