



Motori Monofase - IE2

MOTORI BITENSIONE

- Personalizzazione a tutti i livelli
- Versione bitensione **115/230 V**



TECHNICAL DATA

Motor Type

AMD 63Z AA4 - 0.11 kW - 4 poles - 115-230V - 50Hz

PERFORMANCE DATA

Type	AMD 63Z AA
Poles	4
kW	0.11
HP	0.15
rpm	1370
η 100%	53
cos Phi	0.89
I_N 115-230V	2.2-1.1
I_A/I_N	2.0
M_A/M_N	0.8
M_K/M_N	1.6
$J \cdot 10^{-3} \text{ kgm}^2$	0.27
kg	4.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	38

Electrical Data

Voltage	115-230V - 50Hz
Connection	115/230V
Running Capacitor value Microf	12.5
Starting Capacitor value Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.