



Motori Monofase - IE2

MOTORI BITENSIONE

- Personalizzazione a tutti i livelli
- **Versione bitensione 115/230 V**



TECHNICAL DATA

Motor Type AMD 100L BA6 - 1.5 kW - 6 poles - 115-230V - 50Hz

PERFORMANCE DATA

Type	AMD 100L BA
Poles	6
kW	1.5
HP	2
rpm	890
η 100%	74
cos Phi	0.98
I_N 115-230V	18-9
I_A/I_N	2.9
M_A/M_N	0.5
M_K/M_N	1.4
J 10⁻³ kgm²	9.43
kg	22.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	51

Electrical Data

Voltage	115-230V - 50Hz
Connection	115/230V
Running Capacitor value Microf	-
Starting Capacitor value Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.