



Motori Monofase - IE2

MOTORI BITENSIONE

- Personalizzazione a tutti i livelli
- **Versione bitensione 115/230 V**



TECHNICAL DATA

Motor Type

AMDE 63Z BA2 - 0.18 kW - 2 poles - 115-230V - 50Hz

PERFORMANCE DATA

Type	AMDE 63Z BA
Poles	2
kW	0.18
HP	0.25
rpm	2800
η 100%	55
cos Phi	0.98
I_N 115-230V	2.9-1.45
I_A/I_N	3.0
M_A/M_N	1.6
M_K/M_N	1.6
J 10 ⁻³ kgm ²	0.14
kg	5.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	115-230V - 50Hz
Connection	115/230V
Running Capacitor value Microf	-
Starting Capacitor value Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.