



Motori Monofase - IE2

MOTORI BITENSIONE

- Personalizzazione a tutti i livelli
- **Versione bitensione 115/230 V**



TECHNICAL DATA

Motor Type

AMDE 71Z AA4 - 0.24 kW - 4 poles - 115-230V - 50Hz

PERFORMANCE DATA

Type	AMDE 71Z AA
Poles	4
kW	0.24
HP	0.32
rpm	1300
η 100%	51
cos Phi	0.81
I_N 115-230V	5.1-2.55
I_A/I_N	2.5
M_A/M_N	2.3
M_K/M_N	1.4
J 10 ⁻³ kgm ²	0.82
kg	7.2

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	115-230V - 50Hz
Connection	115/230V
Running Capacitor value Microf	-
Starting Capacitor value Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.